



Wire-end ferrules, Max. wire cross-section: 16 mm², Length: 38 mm, Length of copper pipe: 25 mm, Colour: Green

Business data

| Article number | <u>3025.0</u> |
|--|---------------|
| Article name | HZL 16,0 L GN |
| GTIN (EAN) | 4044211057398 |
| Colour | Green |
| Packaging unit | 50 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 0.21 g |
| Weight per piece (including packaging) | 0.22 g |
| Unit of weight | G |
| Customs number | 85369010 |
| Country of origin | DE |
| Product description | Ferrules |
| | |

Data sheet





| Technical data | | |
|----------------------------------|--------------------------------|--|
| Dimensions | | |
| Length | 38 mm | |
| Length of copper pipe | 25 mm | |
| Width of plastic collar | 9.5 mm | |
| Height of plastic collar | 17.2 mm | |
| Diameter of copper pipe | 8.3 mm | |
| Wall thickness of copper pipe | 0.3 mm | |
| Wall thickness of plastic collar | 0.6 mm | |
| Connection data | | |
| Wire cross-section, max. | 16 mm² | |
| Wire cross-section AWG, max. | 6 | |
| Stripping length | 29 mm | |
| 2-wire plastic collar | ✓ | |
| Materials | | |
| Copper pipe | Copper alloy | |
| Surface | Galvanically tin-plated, shiny | |
| Plastic collar | Polypropylene homopolymer | |
| Working temperature, min. | -5 °C | |
| Working temperature, max. | 105 °C | |
| Further technical data | | |
| Insulation available | ✓ | |
| Environmental Product Compliance | | |
| REACH Conform | yes | |
| REACH Reference date | 2022-06-10 | |
| REACH Candidate Substance Note | No | |
| RoHS Conform | yes | |



| Approvals | | |
|---------------------------|-----|--|
| Standards and regulations | | |
| DIN 46228-4:1990 | yes | |



Media



Accessories