

# 48-Device AC Mobile Charging Cart - Laptops and Chromebooks, 120V, NEMA 5-15P, 10 ft. (3.05 m) Cord, Black

MODEL NUMBER: CSC48AC











Charges, secures and organizes up to 48 Chromebooks and laptops in education, healthcare, retail, warehouse and office environments.

#### **Features**

**Mobile Charging Cart Accommodates up to 48 Chromebooks and Laptops**This 120V charging cart provides timed AC charging, secure storage and cord management for as many as 48 Chromebooks and laptops. The connected devices' AC adapters plug into 48 NEMA 5-15R outlets, which provide up to 1,440 watts for charging. A built-in circuit breaker protects the devices against overloads.

**High-Speed Zone Charging Conserves Energy and Helps Avoid Potential Overloads**The 48 NEMA 5-15R outlets are split evenly into two color-coded charging zones to support more devices and higher wattages without overloads. A built-in timer alternates charging zones every hour. LEDs indicate which zone is being charged at any given time.

Locking Steel Enclosure Keeps Valuable Equipment Safe and Secure Constructed from heavy-duty steel covered with a black powder-coated finish, this laptop charging cart provides safe, secure storage. Devices and their power adapters are stored in separate compartments. The front and back doors lock with the included keys to help prevent theft, damage and tampering. For extra security, the front door can be fastened with a user-supplied padlock. Flow-through ventilation helps protect against overheating, and the specially coated shelves help prevent device scratches and scuffs.

**Moving Your Devices from Room to Room Is Easy**Large swivel casters with non-marking wheels improve the ride over uneven surfaces and lock to help prevent unwanted movement. The reversible wide-grip handle makes the cart easy to control. Corner safety bumpers protect walls and doorways from scratches. The compact Chromebook charging cart takes up about the same amount of physical space as a typical A/V cart.

Well-Organized to Avoid Confusing Cable ClutterHeavy power adapters store out of the way in removable baskets. Cables and connectors run through zoned slots and an overhead cable manager, keeping them organized and out of the way. Adjustable dividers accommodate up to 16 devices per shelf, and device spaces are numbered for easy identification. A power cord wrap keeps the input cord out of the way when moving the charging station. The 10-ft. (3.05 m) cord with space-saving right-angle NEMA 5-15P plug allows great flexibility in reaching AC outlets.

### **Highlights**

- 48 internal NEMA 5-15R outlets provide up to 1,440 total watts for charging
- Hourly timer alternates charging zones to help prevent overloads
- In-cabinet RJ45 jack connects Ethernet peripherals, including routers and hotspots
- Dual external NEMA 5-15R outlets provide power for a monitor or projector
- 10-ft. (3.05 m) cord with NEMA 5-15P plug allows great flexibility in reaching AC outlets

## **Applications**

- Charge up to 48 Chromebooks and laptops in schools, businesses and government organizations that rely on the daily use of mobile devices
- Easily and safely transport connected devices from room to room
- Use the laminate top as a workstation or a sturdy platform for A/V equipment

#### **Package Includes**

- CSC48AC 48-Device AC Charging Station Cart, Black
- Cart handle
- Input cord wrap
- (6) Protective bumpers
- (10) Hex screws
- Hex key
- (2) Keys
- Owner's manual



Laminated Wood-Grain Top Doubles as a Convenient WorkstationThe laminated top acts as a smooth writing surface and holds a projector, monitor or other peripherals that plug into two external NEMA 5-15R outlets controlled by an inside on/off switch. A pass-through RJ45 jack is provided for connecting Ethernet devices, such as a wireless router or hotspot, inside the cabinet.

# **Specifications**

OVERVIEW		
UPC Code	037332226075	
Product Type	Multi-Device Charger	
Charging Form Factor	Mobile Cart	
Functions	Charge; Secure	
Device Compatibility	Chromebook; Laptop	
Device Slots	48	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Voltage Compatibility (VAC)	120	
Input Frequency	60 Hz	
Input Plug Type	NEMA 5-15P	
Input Cord Length (ft.)	10	
Input Cord Length (m)	3.05	
CHARGING		
Number of Charging Ports	48	
Charging Method	AC	
Charging Port Type	NEMA 5-15R	
Charging Ports Details	Pass through	
Charging Ports / Amps	(48) 12A	
Overcharge Protection	No	
Charging Amps per Port	12A	
PHYSICAL		
Color	Black	
Material of Construction	Steel	
Charging Station Form Factor	Mobile Cart	
Shipping Dimensions (hwd / in.)	46.85 x 26.77 x 29.13	
Shipping Weight (kg)	92.99	



Sinct Dimensions - Bottom (hwd / in.)   10.11 x 1.05 x 15.58     Sinct Dimensions - Bottom (hwd / in.)   10.13 x 1.05 x 15.58     Sinct Dimensions - Middle (hwd / in.)   10.13 x 1.05 x 15.58     Sinct Dimensions - Middle (hwd / in.)   10.13 x 1.05 x 15.58     Sinct Dimensions - Top (hwd / min)   10.13 x 1.05 x 15.58     Sinct Dimensions - Top (hwd / min)   257.3 x 26.79 x 395.72     Unit Dimensions (hwd / in.)   40.500 x 26.79 x 395.72     Unit Dimensions (hwd / in.)   40.500 x 26.040 x 28.640     Unit Dimensions (hwd / in.)   40.950 x 26.040 x 28.640     Unit Weight (kip.)   47.82     Unit Weight (kip.)   49.8     Sasembly Required   76.8     Antimicrobial   No     EMURET Line Noise Protection   No     Lacking   Yes     Lack Type   Key     P88 Rated   No     Built-in Circuit Breaker   Yes     Flow-Through Ventilation   Yes     Flow-Through Ventilation   Yes     Flow-Through Ventilation   No     P20 Rated   No     STANDARDS & COMPLIANCE     Flow-Through Ventilation   CANUCSA-C22.2 No. 60950-1 (Canada); NOM (Mesico); UL 60950-1     Florduct Compliance   Rohis CE (Europe); REACH; FCC (USA)    WARRANTY & SUPPORT			
March   Marc	Slot Dimensions - Bottom (hwd / in.)	10.11 x 1.05 x 15.58	
Slot Dimensions - Middle (hwd / mm)         257,3 x 26.79 x 395.72           Slot Dimensions - Top (hwd / m)         10.13 x 1.05 x 15.58           Slot Dimensions (hwd / m)         43.050 x 26.040 x 28.840           Unit Dimensions (hwd / m)         190.35 x 66.14 x 73.25 (con la manija instalada)           Unit Weight (lbs)         147.82           Unit Weight (lcg)         67.05           Number of Shelves         3           Assembly Required         Yes           FEATURES & SPECIFICATIONS*           Cord Management         Yes           Antimicrobial         No           Locking         Yes           Locking         Yes           Lock Type         Key           P68 Rated         No           Built-In Circuit Breaker         Yes           Uv Sterilization         Yes           Lov Sterilization         Yes           Lov Sterilization         No           Uv Sterilization         No           Loz Cated         No           Vesterilization         No           Loz Cated         No           Visterilization         No           Loz Cated         No           Visterilizations         Ro Cate Cate Cate Cate Cate Cate Ca	Slot Dimensions - Bottom (hwd / mm)	256.9 x 26.79 x 395.72	
Sibt Dimensions - Top (hwd / in.)         10.13 x 1.05 x 15.58           Sibt Dimensions - Top (hwd / mm)         257.3 x 26.79 x 395.72           Unit Dimensions (hwd / in.)         43.050 x 26.040 x 28.840           Unit Dimensions (hwd / cm)         109.35 x 66.14 x 73.25 (con la manija instalada)           Unit Weight (lbs.)         147.82           Unit Weight (kg)         67.05           Number of Shelves         3           Assembly Required         Yes           FEATURES & SPECIFICATIONS           Cord Management         Yes           Antimicrobial         No           Locking         Yes           Lock Type         Key           H968 Rated         No           Suilt-In Circuit Breaker         Yes           Vovecurrent Protection         Yes           Flow-Through Ventilation         Yes           UV Sterilization         No           UV Sterilization         No           STANDARDS & COMPLIANCE         Yes           Product Certifications         CANICSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1           Product Compliance         RoHS; CE (Europo); REACH; FCC (USA)    **CATEGORY PAGE FILTERS (YN V-V)	Slot Dimensions - Middle (hwd / in.)	10.13 x 1.05 x 15.58	
Sit Dimensions - Top (nwd / mm)	Slot Dimensions - Middle (hwd / mm)	257.3 x 26.79 x 395.72	
Unit Dimensions (hwd / in)         43.050 x 26.040 x 28.840           Unit Dimensions (hwd / em)         109.35 x 66.14 x 73.25 (con la manija instalada)           Unit Weight (lbs.)         147.82           Unit Weight (kg)         67.05           Number of Shelves         3           Assembly Required         Yes           FEATURES & SPECIFICATIONS           Cord Management         Yes           Antimicrobial         No           EMI/RFI Line Noise Protection         No           Locking         Yes           Lock Type         Key           IP88 Rated         No           Built-in Circuit Breaker         Yes           Overcurrent Protection         Yes           Ves Sterilization         No           IP20 Rated         No           STANDARDS & COMPLIANCE           Product Certifications         CAN/CSA-C22.2 No. 80950-1 (Canada); NOM (Mexico); UL 60950-1           Product Compliance           ARRANTY & SUPPORT           Product Warranty Period (Worldwidg)         2-year limited warranty	Slot Dimensions - Top (hwd / in.)	10.13 x 1.05 x 15.58	
Unit Dimensions (hwd / cm)         109.35 x 66.14 x 73.25 (con la manija instalada)           Unit Weight (bg.)         147.82           Unit Weight (kg)         67.05           Number of Shelves         3           Assembly Required         Yes           FEATURES & SPECIFICATIONS           Cord Management         Yes           Antimicrobial         No           EMI/RFI Line Noise Protection         No           Lock Type         Key           Lock Type         Key           Built-in Circuit Breaker         Yes           Overcurrent Protection         Yes           Volverurent Protection         Yes           Flow-Through Ventilation         Yes           UV Sterilization         No           STANDARDS & COMPLIANCE           Product Certifications         CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1           Product Compliance         RoHS; CE (Europe); REACH; FCC (USA)           WARRANTY & SUPPORT           Product Warranty Period (Wortfowide)         2-year limited warranty	Slot Dimensions - Top (hwd / mm)	257.3 x 26.79 x 395.72	
Unit Weight (kg)         147.82           Unit Weight (kg)         67.05           Number of Shelves         3           Assembly Required         Yes           FEATURES & SPECIFICATIONS           Features & SPECIFICATIONS           Cord Management         Yes           Antimicrobial         No           EMI/RFI Line Noise Protection         No           Locking         Yes           Lock Type         Key           Lock Type         Key           Built-In Circuit Breaker         Yes           Overcurrent Protection         Yes           Viscerilization         No           UV Sterilization         No           UV Sterilization         No           STANDARDS & COMPLIANCE           Product Certifications         CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1           Product Compliance         Rolls; CE (Europe); REACH; FCC (USA)           WARRANTY & SUPPORT           Product Warranty Period (Worldwide)         2-year limited warranty	Unit Dimensions (hwd / in.)	43.050 x 26.040 x 28.840	
Unit Weight (kg)         67.05           Number of Shelves         3           Assembly Required         Yes           FEATURES & SPECIFICATIONS           Cord Management         Yes           Antimicrobial         No           EMI/RFI Line Noise Protection         No           Locking         Yes           Lock Type         Key           IP68 Rated         No           Built-In Circuit Breaker         Yes           Overcurrent Protection         Yes           IV Sterilization         No           IP20 Rated         No           STANDARDS & COMPLIANCE           Product Certifications         CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1           Product Compliance           RARRANTY & SUPPORT           Product Warranty Period (Worldwide)         2-year limited warranty           CATEGORY PAGE FILTERS (YN ONLY)	Unit Dimensions (hwd / cm)	109.35 x 66.14 x 73.25 (con la manija instalada)	
Number of Shelves 3 Assembly Required Yes  FEATURES & SPECIFICATIONS  Cord Management Yes Antimicrobial No EMI/RFI Line Noise Protection No Locking Yes Lock Type Key IP68 Rated No Built-In Circuit Breaker Yes Overcurrent Protection Yes IVV Sterilization No IP20 Rated No IP20 Rated No STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance Roths (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide) 2-year limited warranty  CATEGORY PAGE FILTERS (YN V-V)	Unit Weight (lbs.)	147.82	
FEATURES & SPECIFICATIONS  Cord Management Yes Antimicrobial No EMI/RFI Line Noise Protection No Locking Yes Lock Type Key IP68 Rated No Built-In Circuit Breaker Yes Overcurrent Protection Yes Flow-Through Ventilation Yes UV Sterilization No IP20 Rated No STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Voorlied Warranty)  CATEGORY PAGE FILTERS (VIN ONLY)	Unit Weight (kg)	67.05	
FEATURES & SPECIFICATIONS  Cord Management Yes  Antimicrobial No  EM//RFI Line Noise Protection No  Locking Yes  Lock Type Key  IP68 Rated No  Built-In Circuit Breaker Yes  Overcurrent Protection Yes  Flow-Through Ventilation Yes  UV Sterilization No  IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Voorlimited warranty)  CATEGORY PAGE FILTERS (YN NULY)	Number of Shelves	3	
Cord Management Yes Antimicrobial No EMI/RFI Line Noise Protection No Locking Yes Lock Type Key IP68 Rated No Built-In Circuit Breaker Yes Overcurrent Protection Yes Flow-Through Ventilation Yes UV Sterilization No IP20 Rated No  STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT Product Warranty Period 2-year limited warranty  CATEGORY PAGE FILTERS (Y/N OLV)	Assembly Required	Yes	
Antimicrobial No  EMI/RFI Line Noise Protection No  Locking Yes  Lock Type Key  IP68 Rated No  Built-In Circuit Breaker Yes  Overcurrent Protection Yes  Flow-Through Ventilation Yes  UV Sterilization No  IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period 2-year limited warranty  CATEGORY PAGE FILTERS (YN NLY)	FEATURES & SPECIFICATIONS		
Antimicrobial No  EMI/RFI Line Noise Protection No  Locking Yes  Lock Type Key  IP68 Rated No  Built-In Circuit Breaker Yes  Overcurrent Protection Yes  Flow-Through Ventilation Yes  UV Sterilization No  IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period 2-year limited warranty  CATEGORY PAGE FILTERS (YN NLY)	Cord Management	Yes	
Locking Yes  Lock Type Key  IP68 Rated No  Built-In Circuit Breaker Yes  Overcurrent Protection Yes  Flow-Through Ventilation Yes  UV Sterilization No  IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide)  CATEGORY PAGE FILTERS (Y/N ONLY)		No	
Lock Type Key IP68 Rated No Built-In Circuit Breaker Yes Overcurrent Protection Yes Flow-Through Ventilation Yes UV Sterilization No IP20 Rated No  STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT Product Warranty Period (Worldwide) 2-year limited warranty	EMI/RFI Line Noise Protection	No	
IP68 Rated No Built-In Circuit Breaker Yes Overcurrent Protection Yes Flow-Through Ventilation Yes UV Sterilization No IP20 Rated No  STANDARDS & COMPLIANCE Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1 Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT Product Warranty Period (Worldwide) 2-year limited warranty	Locking	Yes	
Built-In Circuit Breaker Yes  Overcurrent Protection Yes  Flow-Through Ventilation Yes  UV Sterilization No  IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide) 2-year limited warranty	Lock Type	Key	
Overcurrent Protection Yes  Flow-Through Ventilation Yes  UV Sterilization No  IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide) 2-year limited warranty  CATEGORY PAGE FILTERS (Y/N ONLY)	IP68 Rated	No	
Flow-Through Ventilation Yes  UV Sterilization No  IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide) 2-year limited warranty	Built-In Circuit Breaker	Yes	
UV Sterilization No  IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide) 2-year limited warranty  CATEGORY PAGE FILTERS (Y/N ONLY)	Overcurrent Protection	Yes	
IP20 Rated No  STANDARDS & COMPLIANCE  Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide) 2-year limited warranty  CATEGORY PAGE FILTERS (Y/N ONLY)	Flow-Through Ventilation	Yes	
STANDARDS & COMPLIANCE  Product Certifications	UV Sterilization	No	
Product Certifications CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1  Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide) 2-year limited warranty  CATEGORY PAGE FILTERS (Y/N ONLY)	IP20 Rated	No	
Product Compliance RoHS; CE (Europe); REACH; FCC (USA)  WARRANTY & SUPPORT  Product Warranty Period (Worldwide) 2-year limited warranty  CATEGORY PAGE FILTERS (Y/N ONLY)	STANDARDS & COMPLIANCE		
WARRANTY & SUPPORT  Product Warranty Period (Worldwide)  2-year limited warranty  CATEGORY PAGE FILTERS (Y/N ONLY)	Product Certifications	CAN/CSA-C22.2 No. 60950-1 (Canada); NOM (Mexico); UL 60950-1	
Product Warranty Period (Worldwide)  2-year limited warranty  CATEGORY PAGE FILTERS (Y/N ONLY)	Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
(Worldwide) 2-year inflited warranty  CATEGORY PAGE FILTERS (Y/N ONLY)	WARRANTY & SUPPORT		
	Product Warranty Period (Worldwide)	2-year limited warranty	
External Receptacle Yes	CATEGORY PAGE FILTERS (Y/N ONLY)		
	External Receptacle	Yes	







© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.